

G86 AND G88NR® RACK AND PINION STEERING SYSTEMS

A COMPLETE STEERING SYSTEM CONSISTS OF:

- Preassembled helm with steering cable:
M86
- Helm assembly:
G86 - 39418 G standard
G88NR® - 39419 J - non reversible
- Mounting bezel:
X34 - 36654 B - black, 90° mounting
X34W - 40654 C - white, 90° mounting
X35 - 36655 C - black, 20° mounting
- Optional steering wheel (see index)
- Engine connection kits (see index)

FEATURES AND TECHNICAL SPECIFICATIONS:

- Easy and safe steering: patented non reversible G88NR helm eliminates the continuous load on the operator caused by the propeller torque
- All stainless steel cable output ends
- Made exclusively in corrosion resistant materials
- Optional 90° or 20° installation
- Standard 3/4" tapered shaft
- Lock-to-lock steering wheel turns: 3,5
- Stroke: 8.2" (210 mm)
- Maximum allowable steering wheel diameter: 16.5" (420 mm)
- Minimum steering cable bend radius: 7,9" (200 mm)
- G86 and G88 NR steering systems are not to be used on boats equipped with engines that exceed the maximum horsepower rating of the boat
- Available in package with RACKTECH and ACCUTECH (see page 20)
- Exceeds EN 28848 safety standards
- Exceeds ABYC P17 safety standards

